



Metl-Span CF PIR Insulated Panels Weight in PSF

Thickness	Panel Type	Facing Gage (Face 1/Face 2)					
		26/26	24/26	22/26	24/24	22/24	22/22
2"	CF-44	2.07	2.35	2.63	2.62	2.89	3.16
	CF-42	2.08	2.36	2.64	2.63	2.91	3.17
	CF-36	2.11	2.40	2.68	2.67	2.95	3.22
	CF-30	2.15	2.45	2.74	2.72	3.02	3.29
2.5"	CF-44	2.19	2.46	2.74	2.73	3.01	3.27
	CF-42	2.19	2.47	2.75	2.74	3.02	3.29
	CF-36	2.22	2.51	2.79	2.78	3.07	3.34
	CF-30	2.26	2.56	2.85	2.83	3.13	3.41
3"	CF-44	2.30	2.58	2.85	2.84	3.12	3.39
	CF-42	2.31	2.59	2.87	2.85	3.13	3.40
	CF-36	2.34	2.62	2.91	2.89	3.18	3.45
	CF-30	2.38	2.67	2.96	2.95	3.24	3.52
4"	CF-44	2.52	2.80	3.08	3.07	3.34	3.61
	CF-42	2.53	2.81	3.09	3.08	3.36	3.62
	CF-36	2.56	2.85	3.13	3.12	3.40	3.67
	CF-30	2.60	2.90	3.19	3.17	3.47	3.74
5"	CF-44	2.75	3.03	3.30	3.29	3.57	3.84
	CF-42	2.76	3.04	3.32	3.30	3.58	3.85
	CF-36	2.79	3.07	3.36	3.34	3.63	3.90
	CF-30	2.83	3.12	3.41	3.40	3.69	3.97
6"	CF-44	2.97	3.25	3.53	3.52	3.79	4.06
	CF-42	2.89	3.26	3.54	3.53	3.81	4.07
	CF-36	3.01	3.30	3.58	3.57	3.85	4.12
	CF-30	3.05	3.35	3.64	3.62	3.92	4.19
8"	CF-44	3.42	3.70	3.98	3.97	4.24	4.51
	CF-42	3.43	3.71	3.99	3.98	4.26	4.52
	CF-36	3.46	3.75	4.03	4.02	4.30	4.57
	CF-30	3.50	3.80	4.09	4.07	4.37	4.64

Notes:

The above numbers are based on a core density of 2.20 pcf

The weights of the different panel facings are as follows:

26 gage: 0.7752 psf

24 gage: 0.9792 psf

22 gage: 1.224 psf